

# SMART STRING ENERGY STORAGE SYSTEM

LUNA2000-7/14/21-S1



### Flexible Capacity

6.9 kWh per Battery Module  
Scalable from 6.9 kWh to 20.7 kWh per Group  
Max. 4 Groups with 82.8 kWh for an Inverter<sup>8</sup>



### More Usable Energy

Module+ Architecture, Built-in Energy Optimizer  
Ultra-long Service Time  
100% Depth of Discharge



### 5-layer Safety Protection

Cell-level, Electrical-level, Structural-level  
Active Protection, Emergency Protection



### Ultimate Use Experience

-20 °C to +55 °C Operating Temperature  
Max 10.5kW Charging & Discharging Power per Group  
Super Quiet Operation



### Easy Installation

Cable Free Connection Between Modules  
Horizontal Adjustment Design  
Quick Commissioning



### Aesthetically Pleasing Design

Breathing Star Ring Display  
Silky Curve Design  
Simplistic and Borderless

# LUNA2000-7/14/21-S1 Technical Specification



Performance			
Power module	LUNA2000-10KW-C1		
Number of power modules	1		
Battery module	LUNA2000-7-E1		
Battery module energy	6.9 kWh		
Number of battery modules	1	2	3
Battery usable energy <sup>1</sup>	6.9 kWh	13.8 kWh	20.7 kWh
Max. charging & discharging power	3.5 kW	7 kW	10.5 kW
Operating voltage range (single-phase system)	350 ~ 560 V		
Operating voltage range (three phase system)	600 ~ 980 V		
Communication			
Display	SOC status indicator, LED indicator		
Communication <sup>2</sup>	RS485/FE/CAN		
General Specification			
Dimensions (W x D x H)	590 mm x 255 mm x 510 mm	590 mm x 255 mm x 870 mm	590 mm x 255 mm x 1230 mm
Weight (Floor stand toolkit included)	80 kg	148 kg	216 kg
Power module dimension (W x D x H)	590 mm x 255 mm x 150 mm		
Power module weight	10 kg		
Battery module dimensions (W x D x H)	590 mm x 255 mm x 360 mm		
Battery module weight <sup>3</sup>	68 kg (110.2 lb) <sup>2</sup>		
Installation	Floor stand (standard), Wall mount (optional)		
Operating temperature <sup>4</sup>	-20°C to +55°C (-4°F to +131°F)		
Max. operating altitude <sup>5</sup>	4,000 m (13,123 ft.) (Derating above 2,000 m)		
Environment <sup>6</sup>	Outdoor / Indoor		
Relative humidity	5% ~ 95%		
Cooling	Natural convection		
IP rating	IP 66		
Noise emission	< 29 dB <sup>7</sup>		
Cell technology	Lithium-iron phosphate (LiFePO <sub>4</sub> )		
Scalability <sup>8</sup>	Max. 4 systems in parallel operation		
Compatible inverters <sup>9</sup>	SUN2000-2/3/3.68/4/4.6/5/6KTL-L1, SUN2000-8/10K-LC0 SUN2000-3/4/5/6/8/10KTL-M1, SUN2000-12/15/17/20/25K-MB0		
Standards Compliance (More Available Upon Request)			
Certificates	CE, RCM, CEC, VDE2510-50, IEC62619, IEC 60730, UN38.3, ISO13849, REACH, RoHS		
Ordering and Deliverable Part			
Available for ordering <sup>10</sup>	LUNA2000-7-E1, LUNA2000-10KW-C1, Wall Mounting Bracket for LUNA2000-7/14/21-S1		

\*1 Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C, at the beginning of service life.

\*2 CAN is for communication between energy storage in parallel scenarios only. Launch time of FE communication is to be determined, please confirm with your local product manager of Huawei for final version.

\*3 The weight of the battery modules varies with products, with a tolerance of ±3%.

\*4 The output power may be affected by temperature. Please refer to the output derating curve for details.

\*5 The output power may be affected by altitude. Please refer to the output derating curve for details.

\*6 Outdoor installation is recommended. For indoor installation instructions, please refer to the user manual.

\*7 The data is from Huawei lab, and the test condition is 1m distance and typical working voltage.

\*8 Only SUN2000-12/15/17/20/25K-MB0 supports 4 energy storage systems in parallel operation.

\*9 For details on the timetable of compatibility with SUN2000-8/10K-LC0 and SUN2000-2/3/3.68/4/4.6/5/6KTL-L1, please confirm with your local product manager of Huawei for final version.

\*10 The power module and battery modules of the storage system are separately order in the required quantity.

Disclaimer: the preceding values are measured by an internal laboratory of Huawei in a specific environment. The actual values may vary with products, software versions, usage conditions, and environmental factors.

# Smart String Energy Storage System



## Meer beschikbare energie

100% ontladen  
Op module niveau energie optimaliseren



## Flexibel Investeren

5kWh modulair ontwerp,  
Schaalbaar van 5 tot 30 kWh



## Veilig & Betrouwbaar

Lithium -ijzerfosfaat (LFP) Cell



## Gemakkelijk installeren

12 kg Voedingsmodule  
50 kg Batterij Module






## Snelle Inbedrijfstelling

Automatisch gedetecteerd in de App



## Perfect toepasbaar

Toepasbaar voor residentiële  
een- & drie-fase omvormers

	LUNA2000-5-S0	LUNA2000-10-S0	LUNA2000-15-S0
Technische specificaties			

Prestaties			
Voedingsmodule	LUNA2000-5KW-C0		
Aantal voedingsmodules	1		
Batterij module	LUNA2000-5-E0		
Batterij module energie	5 kWh		
Aantal batterij modules	1	2	3
Batterij beschikbare energie	5 kWh	10 kWh	15 kWh
Max. uitgangsvermogen	2.5 kW	5 kW	5 kW
Piek uitgangsvermogen	3.5 kW, 10 s	7 kW, 10 s	7 kW, 10 s
Nominale spanning (1-fase systeem)	360 V		
Spanningsbereik (1-fase systeem)	350 – 560 V		
Nominale spanning (3-fasen systeem)	600 V		
Spanningsbereik (3-fasen systeem)	600 – 980 V		

Communicatie	
Display	SoC indicatie, LED indicatie
Communicatie	RS485 / CAN (alleen voor parallel gebruik)

Algemene Specificaties			
Afmetingen (B*D*H)	670 * 150 * 600 mm	670 * 150 * 960 mm	670 * 150 * 1320 mm
Gewicht (Vloeropstelling toolkit inclusief)	63.8 kg	113.8 kg	163.8 kg
Voedingsmodule afmetingen (B*D*H)	670 * 150 * 240 mm		
Voedingsmodule gewicht	12 kg		
Batterij module afmetingen (B*D*H)	670 * 150 * 360 mm		
Batterij module gewicht	50 kg		
Installatie	Vloeropstelling (standaard), Muur ophanging (optioneel)		
Temperatuur tijdens gebruik	-10°C ~ + 55°C <sup>1</sup>		
Relatieve vochtigheid	5% ~ 95%		
Koeling	Natuurlijke convectie		
Bedrijfshoogte	0 - 4,000 m (Afleiding boven 2,000 m)		
Beschermingsgraad	IP 65		
Geluidsniveau	<29 dB		
Celtechnologie	Lithium-ijzerfosfaat (LiFePO <sub>4</sub> )		
Garantie	10 jaar <sup>2</sup>		
Schaalbaarheid	Max. 2 systemen parallel		
Toepasbare omvormers	SUN2000L-2/3/3.68/4/4.6/5KTL <sup>3</sup> , SUN2000-2/3/3.68/4/4.6/5/6KTL-L1, SUN2000-3/4/5/6/8/10KTL-M0 <sup>3</sup> , SUN2000-3/4/5/6/8/10KTL-M1		

Standaard normering (meer beschikbaar op aanvraag)	
Certificaten	CE, RCM, CEC, VDE2510-50, IEC62619, IEC 60730, UN38.3

Te bestellen en leverbare onderdelen	
Product bestelcodes <sup>4</sup>	LUNA2000-5KW-C0, LUNA2000-5-E0, LUNA2000 Wall Mounting Bracket

1. Derating van laad/ontlaadstroom vindt plaats bij een bedrijfstemperatuur van -10°C to 5 °C. & 45 °C to 55 °C

2. Zie beschrijving batterij garantie voorwaarden

3. Software update vereist, beschikbaar Q1, 2021

4. Bij bestelling van het opslag systeem dienen de voedingsmodule en de batterij module apart te worden besteld welke vervolgens worden geleverd in de bestelde hoeveelheden.